



ROTATING/FLASHING BEACONS

ROTATING/FLASHING BEACONS



ROTATING/FLASHING BEACONS

NICE TO KNOW – ROTATING/FLASHING BEACONS



With rotating beacons and strobe lights, you warn the environment of your presence.

Rotating beacons and strobe lights exist in 3 different technologies: LED, xenon and halogen.

Depending on the selected technology, a distinction is made between rotating beacons and strobe lights:

- LED technology is used in both rotating beacons and strobe lights. The rotating beacon is created by means of a specific sequence of flashes in the light
- Xenon technology is restricted to the creation of flashes
- Halogen lights use a mirror to project the light beam around

Strobe lights are often bolted onto lift trucks, or attached via a magnet or suction cup. On tractors, a more commonly used method is a 'pole mounting'.

We also have some 'plug-and-play' models available. These are equipped with a magnetic mounting base and a 12V plug and can very easily be (un)installed.

All LED and xenon beacons are supplied including the LED module or Xenon tube. The voltage or voltage range is always mentioned beside the reference. Beacons with halogen or bulb technology are following the same logic. The voltage of the included bulb is mentioned beside the reference and otherwise the spare bulbs are shown below the technical data.

A small range of beacons for priority vehicles are also available. The use of rotating beacons on priority vehicles is restricted. The user must observe the regulations on this subject.

ROTATING/FLASHING BEACONS



LED FLASHING BEACONS


REF 151TA3825

- Technology: LED
- Mounting: magnetic mount
- 3-way switch for flashing or steady-on operation
- IP65
- Requires 4 AA batteries (not included)


REF 106TA9001 – 4 AA batteries

Portable

TOTAL SOURCE®




ROTATING/FLASHING BEACONS



REF 164TA1461 – 10–30V

- Technology: LED
- Mounting: 2 screws
- IP69K

TOTAL SOURCE®




REF 151TA3699 – 24–48V


- Technology: LED
- Mounting: 2 screws
- Center distance: 71 mm
- IP65
- Flash rate: 120 flashes/minute
- Connector: J3 built-in

TOTAL SOURCE®


LED FLASHING BEACONS



- Technology: LED
- Mounting: 2 screws
- Center distance: 90 mm
- IP65
- Flash rate: 120 flashes/minute

TOTAL SOURCE[®]

- Technology: LED (3 pcs)
- Mounting: 3 screws
- Pitch circle: 115 mm
- Wire length: 400 mm
- IP65
- Flash rate: 60 ± 90 flashes/minute
- Economic version

TOTAL SOURCE[®]

- Technology: LED (6 pcs)
- Mounting: 3 screws
- Pitch circle: 115 mm
- Wire length: 290 mm
- IP65
- Flash rate: 60 ± 10 flashes/minute
- Lens not interchangeable


Made in USA

METEORLITE®

ROTATING/FLASHING BEACONS




LED FLASHING BEACONS



REF 151TA3637 - 10-30V


- Technology: LED
- Mounting: 3 screws
- Pitch circle: 115 mm
- Length cable: 95 mm
- IP67
- 12 flash patterns
- Low profile

TOTAL SOURCE®

REF 149TA7223 - 12-30V

- Technology: LED
- Mounting: magnetic suction cap
- Roll cable
- 12V car plug

E-approved

TOTAL SOURCE[®]

REF 149TA5328 - 12-30V


- Technology: LED
- Mounting: magnetic suction cap
- 12V car plug

E-approved

TOTAL SOURCE®


ROTATING/FLASHING BEACONS

LED FLASHING BEACONS




- Technology: LED
- Mounting: 3 screws
- Pitch circle: 126 mm
- Wire length: 170 mm

E-approved

TOTAL SOURCE®

- High-powered LED, 12W
- Technology: LED
- Mounting: 3 bolts
- IP66
- Polycarbonate shockproof lens
- ECE R10

TOTAL SOURCE®


- Technology: LED
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP6K9K
- Low profile

TOTAL SOURCE®

ROTATING/FLASHING BEACONS




LED FLASHING BEACONS




REF 149TA5332 – 10-30V

- Technology: LED
- Mounting: magnetic
- 12V car plug

TOTAL SOURCE[®]

REF 151TA3814 - 12-24V 3 bolt fixation

- Technology: LED
- Mounting: 3 screws
- Pitch circle: 130 mm
- Low profile

TOTAL SOURCE®

REF 151TA3641 – 20-100V

- Technology: LED
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP65
- Flash rate: 60 flashes/minute
- Hardware included
- Low profile



CURTIS

ROTATING/FLASHING BEACONS




ROTATING/FLASHING BEACONS

LED FLASHING BEACONS

REF 151TA3700 – 12–110V

- Technology: LED
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP65
- Flash rate: 60–80 flashes/minute
- 4 flashing patterns




REF 151TA3701 – Lens amber

REF 164TA1466 – Support

Economic


TOTAL SOURCE®



REF 151TA3714 – 10–100V

- Technology: LED
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 350 mm
- IP54
- Flash rate: 50 flashes/minute
- 3 flashing patterns

SIRENA s.p.a.



REF 151TA3723 – 12–48V


- Technology: LED
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 580 mm
- IP69K
- Flash rate: 65 flashes/minute

TOTAL SOURCE®

ROTATING/FLASHING BEACONS




LED FLASHING BEACONS



REF 151TA3786 - 12-48V


- Technology: LED
- Mounting: magnetic mount
- Flash rate: 65 flashes/minute
- 12V car plug

TOTAL SOURCE[®]

REF 151TA3719 - 10-30V

- Technology: LED
- Mounting: 3 screws
- Pitch circle 130 mm
- Wire length: 630 mm
- IP54
- 11 flash patterns

E-approved

TOTAL SOURCE®

REF 151TA3759 – 12-80V


- Technology: LED
- Mounting: 2 screws
- Center distance: 86 mm
- IP66
- Flash rate: 60 ± 10 flashes/minute
- Low profile

REF 151TA3758 – Protection guard


Made in USA

METEORLITE®

LED FLASHING BEACONS




- Technology: LED
- Mounting: 2 screws
- Center distance: 86 mm
- Wire length: 400 mm
- Connector: 1 x F1, 1 x G1
- Hardware included

TOTAL SOURCE[®]

Made in USA

METEORLITE®



Made in USA

METEORLITE®


ROTATING/FLASHING BEACONS



LED FLASHING & ROTATING BEACON

REF 151TA3782 – Batteries

- Technology: LED
- Mounting:
 - magnetic mount
 - adapter plugs
 - suction pads
 - extra screws
- Wire length: 1520 mm
- IP66
- Flash rate: 60 flashes/minute
- Included:
 - car 12–24V DC charger
 - domestic 100–240V AC
 - 6 rechargeable AA batteries




TOTAL SOURCE®

ROTATING/FLASHING BEACONS

XENON FLASHING BEACONS

REF 151TA3823 – 24V


- Technology: xenon
- Mounting: 2 screws
- Center distance: 130 mm
- Wire length: 450 mm
- Flash tube not replaceable
- Connector: E3



TOTAL SOURCE®

REF 151TA3824 – 12–110V

- Technology: xenon
- Mounting: 2 screws
- Wire length: 215 mm
- Nominateal power: $\pm 3W$
- IP66
- 72 flashes/minute
- Flash tube included



REF 151TA2306 – Lens amber

REF 106TA9146 – Protection guard

REF 106TA9126 – Flash tube


TOTAL SOURCE®

ROTATING/FLASHING BEACONS



ROTATING/FLASHING BEACONS


XENON FLASHING BEACONS



REF 151TA3650 – 10-100V


- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP54
- Flash tube not replaceable
- Low profile

REF 151TA3649 - Lens amber



REF 151TA3634 - 10-32V

- Technology: xenon
- Mounting: 2 screws
- Center distance: 45 mm
- Wire length: 530 mm
- IP67
- Flash tube included
- Connector: C2



REF 151TA3675 – 10-100V without connector

REF 151TA3676 - 10-100V


- Technology: xenon
- Mounting: 2 screws
- Center distance: 45 mm
- Wire length: 460 mm
- IP67
- Flash tube included
- Connector: M2
- Used on Haulotte



ROTATING/FLASHING BEACONS




XENON FLASHING BEACONS



REF 151TA3640 – 10-100V


- Technology: xenon
- Mounting: 2 screws
- Center distance: 50 mm
- Wire length: 400 mm
- IP67
- Flash tube included

TOTAL SOURCE[®]

REF 151TA3635 – 10–100V white

REF 151TA3636 - 10-100V amber

- Technology: xenon
- Mounting: 2 screws
- Center distance: 45 mm
- Wire length: 450 mm
- IP67
- Flash tube included

TOTAL SOURCE[®]

REF 151TA3638 - 12-24V

- Technology: xenon
- Mounting: 2 screws
- Center distance: 50 mm
- IP65
- Flash tube not replaceable

TOTAL SOURCE®


ROTATING/FLASHING BEACONS

ROTATING/FLASHING BEACONS



ROTATING/FLASHING BEACONS

XENON FLASHING BEACONS




REF 151TA3639 - 12-24V

- Technology: xenon
- Mounting: 2 screws
- Center distance: 45 mm
- Wire length: 475 mm
- IP67



CURTIS




REF 151TA3681 - 10-30V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 49 mm
- Wire length: 365 mm
- IP67
- Connector: J2

REF 151TA3683 – Lens

REF 151TA3682 - Flash tube

TOTAL SOURCE®

REF 151TA3684 - 12-24V


- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 45 mm
- Wire length: 340 mm
- Flash tube not replaceable

TOTAL SOURCE®

XENON FLASHING BEACONS



- Technology: xenon
- Mounting: magnetic mount
- Wire length: 1100 mm
- IP66
- Flash rate: 36 flashes/minute
- 12V car plug



REF [151TA3694](#) – Lens amber
REF [151TA2289](#) – Lens red
REF [150TA2426](#) – Lens blue
REF [151TA2290](#) – Lens white
REF [151TA3696](#) – Protection guard
REF [151TA3695](#) – Flash tube


TOTAL SOURCE[®]

Colour	12-110VDC	240AC
Amber	REF 151TA3654	REF 151TA3655
Blue	REF 151TA3657	REF 151TA3658
Clear	REF 151TA3660	REF 151TA3661
Green	REF 151TA3663	REF 151TA3664
Red	REF 151TA3666	REF 151TA3667



- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 115 mm
- IP65
- Flash rate: 60 ± 10 flashes/minute

REF 151TA3656 – Lens amber
REF 151TA3659 – Lens blue
REF 151TA3662 – Lens clear
REF 151TA3665 – Lens green
REF 151TA3668 – Lens red
REF 106TA9126 – Flash tube: 12–110V DC
REF 111TA3637 – Flash tube: 240V AC




Made in USA

METEORLITE®

ROTATING/FLASHING BEACONS



XENON FLASHING BEACONS




REF 151TA3651 – 12-110V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 118 mm
- IP54

REF 160TA1088 – Flash tube




CURTIS



REF 151TA3691 – 10-100V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 490 mm
- IP65
- Flash rate: 75 flashes/minute

TOTAL SOURCE®
BRAND: DELTA DESIGN



REF 151TA3697 – 12-24V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 505 mm
- IP69K
- Flash rate: 125 flashes/minute

REF 151TA3698 – Flash tube

TOTAL SOURCE®
BRAND: ECCO


ROTATING/FLASHING BEACONS

ROTATING/FLASHING BEACONS



ROTATING/FLASHING BEACONS


XENON FLASHING BEACONS



REF 151TA3702 - 12-100V with short cable
REF 151TA3703 - 12-100V with cable 4100 mm
REF 151TA3704 - 12-100V with connector used on
Still and Linde


- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 440 mm
- IP54

REF 106TA9107 - Lens amber

TOTAL SOURCE[®]

REF 151TA3643 - 12-110V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 330 mm
- IP66
- Flash tube not replaceable

TOTAL SOURCE®

REF 151TA3708 – 12– 80V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 465 mm
- IP67
- Flash rate: 72 flashes/minute
- Flash tube not replaceable

REF 151TA3701 – Lens amber
REF 151TA3709 – Protection guard
REF 151TA3710 – Mounting bracket




CURTIS

ROTATING/FLASHING BEACONS




XENON FLASHING BEACONS



REF 151TA2424 - 10-120V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP66
- Flash rate: 75 ± 10 flashes/minute
- Nominuteal power: $\pm 5W$
- Flash tube included


REF 151TA3707 – Flash tube

TOTAL SOURCE[®]

REF 151TA3705 - 10-110V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP65
- Flash rate: 75 flashes/minute
- Nominuteal power: $\pm 7W$
- Flash tube included

REF 151TA3706 – Flash tube

TOTAL SOURCE®

REF 151TA3712 - 10-110V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP65
- Flash rate: 75 ± 10 flashes/minute
- Nominuteal power: $\pm 5W$
- Flash Tube included

REF 151TA3713 – Flash tube

TOTAL SOURCE®


ROTATING/FLASHING BEACONS

ROTATING/FLASHING BEACONS



ROTATING/FLASHING BEACONS

XENON FLASHING BEACONS




REF 151TA3721 – 10-72V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 128 mm
- Wire length: 100 mm
- IP56
- Flash tube included

REF 151TA3722 – Flash tube

TOTAL SOURCE®

FLASHING BEACON WITH AUDIBLE SOUND



REF 151TA3720 – 10-100V


- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP20
- Lens not interchangeable
- Flash tube not replaceable

SIRENA s.p.a.

ROTATING/FLASHING BEACONS




XENON FLASHING BEACONS



REF 151TA3727 – 10–100V without cable


REF 151TA3728 – 10-100V with cable 1695 mm

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP54
- Flash rate: 60 ± 130 flashes/minute



REF 151TA3718 - 10-100V

- Technology: xenon
- Mounting: 3 screws
- Pitch circle 130 mm
- Flash rate: 140 ± 10 flashes/minute



REF 151TA3716 - 10-100V


- Technology: xenon
- Mounting: 3 screws
- Pitch circle 130 mm
- IP54

REF 151TA3717 – Flash tube



ROTATING/FLASHING BEACONS

DOUBLE FLASH XENON STROBE LIGHT




- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 150 mm
- Wire length: 255 mm
- Flash tube included

TOTAL SOURCE[®]

- Technology: xenon
- Mounting: 3 screws
- Pitch circle: 150 mm
- Wire length: 230 mm
- Flash tube included

REF 163TA8752 - Lens amber

TOTALSOURCE®

- Technology: xenon
- Mounting: 3 screws
- Wire length: 150 mm
- IP65
- Flash tube included

REF 150TA2420 - Lens amber

METEORLITE®

ROTATING/FLASHING BEACONS




XENON FLASHING BEACONS



REF 151TA3755 – Wire length: 300 mm, Deutsch connector

REF 151TA3765 – Wire length: 240 mm

- Technology: xenon
- Mounting: 2 screws
- Center distance: 86 mm
- 12–80V
- IP66
- Flash tube included



REF 151TA3757 – Flash tube

REF 151TA3756 – Lens amber

TOTAL SOURCE®



REF 151TA3769 – Amber


REF 151TA3770 – Blue

REF 151TA3772 – Clear

REF 151TA3774 – Green

REF 151TA3776 – Red

- Technology: xenon
- Mounting: 2 screws
- Center distance: 86 mm
- Wire length: 250 mm
- 12–80V
- IP67
- Flash rate: 75 flashes/minute
- Flash tube included



REF 151TA3756 – Lens amber

REF 151TA3771 – Lens blue

REF 151TA3773 – Lens clear

REF 151TA3775 – Lens green

REF 151TA3777 – Lens red


REF 151TA3757 – Flash tube

Made in USA


METEORLITE®

ROTATING/FLASHING BEACONS


XENON FLASHING BEACONS



- Technology: xenon
- Mounting: 2 screws
- Center distance: 86 mm
- Wire length: 420 mm
- IP65
- Flash rate: 60 ± 80 flashes/minute
- Flash tube included

TOTAL SOURCE®

- Technology: xenon
- Mounting: 4 screws
- Pitch circle: 130 mm
- IP55
- Flash tube included




- Technology: xenon
- Mounting: magnetic
- Wire length: 1060 mm
- 72 flashes/minute
- IP65
- Flash tube included
- 12V car plug

TOTAL SOURCE®

ROTATING/FLASHING BEACONS




BULB FLASHING BEACONS



REF 151TA3645 – 48V amber

- Technology: incandescent
- Mounting: 3 screws
- Pitch circle: 99 mm
- IP54
- Flash rate: 160 ± 30 flashes/minute
- Bulb included


REF 119TA8919 – Bulb: BA15D 48V 10W



REF 151TA3648 – 48V yellow

- Technology: incandescent
- Mounting: 3 screws
- Pitch circle: 99 mm
- IP54
- Flash rate: 160 ± 30 flashes/minute
- Bulb included

E-approved



REF 151TA3680 – 24V


- Technology: incandescent
- Mounting: 3 screws
- Pitch circle: 76 mm
- Wire length: 230 mm
- Bulb included

REF 103TA4603 – Bulb: BA15S 24V 21W

TOTALSOURCE®

ROTATING/FLASHING BEACONS

BULB STEADY BEACON



REF 151TA3686 – Without bulb

REF 151TA3687 – 24V with bulb

REF 151TA3688 – 48V with bulb


- Technology: incandescent
- Mounting: 2 screws
- Center distance: 71 mm
- Wire length: 165 mm
- Connector: D2
- Uses flashing module of machine

REF 131TA4780 – Bulb: BA15D 24V 40W

REF 106TA4902 - Bulb: BA15S 48V 40W

TOTAL SOURCE®

HALOGEN ROTATING BEACONS




REF 151TA3726 – 12V

- Technology: halogen
- Mounting: 3 screws
- Pitch circle: 75 mm
- IP54
- Bulb included

REF 150TA5023 – Lens

REF 123TA8005 - Bulb: H1 12V 55W

E-approved



REF 151TA3732 - 24V

- Technology: halogen
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP5K4K, IP9K
- Bulb included

REF 161TA6085 – Bulb: H1 24V 70W

REF 150TA3844 - Lens amber


E-approved



ROTATING/FLASHING BEACONS



HALOGEN ROTATING BEACONS



REF 164TA1463 – 12-24V without bulb


REF 149TA4911 – 12V with bulb

- Technology: halogen
- 12V
- Mounting: 3 screws
- Pitch circle: 130 mm

REF 161TA5353 – Bulb: H1 12V 55W

REF 161TA6085 - Bulb: H1 24V 70W

E-approved

TOTAL SOURCE®


REF 164TA1464

- Technology: halogen
- 12-24V
- Mounting: suction caps
- Bulb not included
- 12V car plug

REF 161TA5353 – Bulb: H1 12V 55W

REF 161TA6085 - Bulb: H1 24V 70W

E-approved

TOTAL SOURCE®

REF [151TA3739](#)

- Technology: halogen
- 12–24V
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 260 mm
- IP54
- Rotation rate: 160 ± 20 rotations/minute
- Bulb not included

REF 123TA8005 – Bulb: H1 12V 55W

REF 123TA8006 - Bulb: H1 24V 70W

E-approved

TOTALSOURCE®

ROTATING/FLASHING BEACONS




ROTATING/FLASHING BEACONS

HALOGEN ROTATING BEACONS

REF 151TA3735

- Type technologie: halogen
- 12-24V
- Mounting: pole mounting, 3 screws
- Pitch circle: 130 mm
- IP55
- Bulb not included



REF 123TA8005 – Bulb: H1 12V 55W

REF 123TA8006 – Bulb: H1 24V 70W

REF 150TA3148 – Lens

E-approved

SIRENA s.p.a.

BULB ROTATING BEACON




REF 151TA3743 – Without bulb

REF 164TA7819 – 36V

REF 151TA3744 – 48V

REF 151TA3745 – 80V

- Technology: incandescent
- 12-80V
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP54
- Rotation rate: 160 ± 30 rotations/minute



REF 106TA9127 – Lens amber

REF 106TA9128 – Lens blue

REF 106TA9129 – Lens green

REF 103TA4664 – Bulb: BA20S 36V 35W

REF 106TA9138 – Bulb: BA20S 48V 35W

REF 123TA8001 – Bulb: BA20S 80V 35W

SIRENA s.p.a.

ROTATING/FLASHING BEACONS




HALOGEN ROTATING BEACONS

REF 151TA3738 – without bulb

REF 151TA3736 – 12V

REF 151TA3737 – 24V

- Technology: halogen
- 12–24V
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP54
- Rotation rate: 160 ± 30 rotations/minute



REF 106TA9127 - Lens amber

REF 106TA9128 - Lens blue

REF 106TA9129 – Lens green

REF 106TA9130 - Lens red


REF 123TA8005 – Bulb: H1 12V 55W

REF 123TA8006 – Bulb: H1 24V 70W

E-approved



ROTATING/FLASHING BEACONS




REF 151TA3715 - 24V

- Technology: halogen
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP55
- Bulb included

REF 123TA8006 – Bulb: H1 24V 70W

E-approved



REF 151TA3729 – Without bulb

REF 151TA3730 - 12V

REF 151TA3731 – 24V

- Type technologie: halogen
- Mounting: 3 screws
- Pitch circle: 130 mm
- IP54
- Rotation rate: 160 ± 30 rotations/minute

REF 151TA3647 – Protection guard

REF 151TA2281 - Support


REF **161TA5353** - Bulb: H1 12V 55W

REF 161TA6085 - Bulb: H1 24V 70W

E-approved



HALOGEN ROTATING BEACONS



REF 151TA3748 – 12V without cable

REF 151TA3749 – 12V with cable


- Technology: halogen
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 120 mm
- IP65
- Rotation rate: 180 ± 30 rotations/minute
- Bulb included

REF 151TA3750 – Protection guard

REF 151TA3751 - Lens amber

REF 144TA5476 – Bulb: H1 12V 55W

E-approved

TOTAL SOURCE[®]

REF 151TA3724 – 12V


- Technology: halogen
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 100 mm
- IP54
- Rotation rate: 160 ± 30 rotations/minute
- Bulb included

REF 144TA5476 – Bulb: H1 12V 55W

E-approved

TOTAL SOURCE®

BRAND: BRITAX



REF 151TA3733 – Without bulb

REF 151TA3734 - 12V

REF 149TA4303 - 24V

- Technology: halogen
- Mounting: 3 screws
- Pitch circle: 130 mm
- Wire length: 185 mm
- IP56
- Rotation rate: 180 rotations/minute
- Bulb not included


REF 123TA8005 – Bulb: H1 12V 55W

REF 123TA8006 - Bulb: H1 24V 70W

E-approved

TOTAL SOURCE®

ROTATING/FLASHING BEACONS




- Technology: halogen
- Mounting: magnetic mount
- Wire length: 550 mm
- IP54
- Rotation rate: 160 rotations/minute
- Bulb included
- 12V car plug

TOTAL SOURCE®
BRAND: BRITAX



75

BULB ROTATING BEACON



- Technology: incandescent
- Mounting: 3 screws
- Pitch circle: 136 mm
- Wire length: 280 mm
- IP23
- Rotation rate: 140 ± 25 rotations/minute
- Bulb included


REF 150TA1314 - Lens amber

TOTAL SOURCE[®][illegible]

- Technology: halogen
- Mounting: magnetic mount
- Wire length: 550 mm
- IP56
- Rotation rate: 180 rotations/minute
- Bulb included
- 12V car plug

REF 151TA3790 - Lens amber

E-approved

TOTAL SOURCE®

- Technology: halogen
- Mounting: magnetic mount and suction cap
- Wire length: 670 mm
- Bulb included
- 12V car plug

E-approved

TOTALSOURCE®


ROTATING/FLASHING BEACONS



HALOGEN BEACONS

REF 151TA3784

- Technology: halogen
- 12-24V
- Mounting: magnetic mount and suction cap
- Wire length: 650 mm
- IP65
- Bulb included
- 12V car plug



REF 151TA2311 – Bulb: BAY9S 12V 21W


REF 151TA2312 - Bulb: BAY9S 24V 21W

E-approved

TOTAL SOURCE®

REF 151TA3791

- Technology: halogeen
- Mounting: magnetic mount
- Wire length: 650 mm
- IP54
- Rotation rate: 160 ± 30 rotations/minute
- Bulb included
- 12V car plug




REF 123TA8005 – Bulb: H1 12V 55W

E-approved



LED ROTATING BEACONS



REF 149TA2683 - 10-30V

- Technology: LED
- Mounting: pole mount
- 3 selectable flash patterns: rotating, double and quad flash

TOTALSOURCE®


ROTATING/FLASHING BEACONS

ROTATING/FLASHING BEACONS



ROTATING/FLASHING BEACONS


LED ROTATING BEACONS



REF 149TA5331 – 10–30V

- Technology: LED
- Mounting: pole mount
- IP6K9K

TOTAL SOURCE®




REF 149TA5303 – 10–30V

- Technology: LED
- Mounting: pole mount

E-approved

TOTAL SOURCE®



REF 164TA1465 – 10–30V

- Technology: LED
- Mounting: pole mount


E-approved

TOTAL SOURCE®

ROTATING/FLASHING BEACONS




LED FLASHING BEACONS



REF 151TA3800 – 12–48V

- Technology: LED
- Mounting: pole mount
- IP69
- Flash rate: 65 flashes/minute

TOTALSOURCE®



REF 151TA3793 – 12V

- Technology: LED
- Mounting: on socket
- IP65
- Flash rate: 60 flashes/minute

TOTALSOURCE®

ROTATING/FLASHING BEACONS

ROTATING/FLASHING BEACONS




ROTATING/FLASHING BEACONS

XENON FLASHING BEACONS

REF 151TA3781 – 12-80V


- Technology: xenon
- Mounting: central bolt
- Wire length: 230 mm
- IP67
- Flash rate: 75 flashes/minute
- Flash tube included



REF 126TA6121 – Flash tube

Made in USA

METEORLITE®



REF 151TA3809 – 12V

- Technology: xenon
- Mounting: pole mount
- IP55
- Flash rate: 140 ± 10 flashes/minute


REF 151TA3810 – Lens amber

SIRENA s.p.a.

ROTATING/FLASHING BEACONS




HALOGEN ROTATING BEACONS



REF 151TA3792 – 12V

- Technology: halogen
- Mounting: pole mount
- IP55
- Rotation rate: 160 ± 30 rotations/minute

REF 123TA8005 – Bulb: H1 12V 55W

TOTAL SOURCE[®]

REF 151TA3794 – Amber

- Technology: halogen
- 12-24V
- Mounting: central bolt M10
- Wire length: 160 mm
- IP56
- Rotation rate: 180 rotations/minute
- Bulb not included
- Connector: 1 x A1, 1 x G1


REF 100TA2093 – Bulb: H1 12V 55W

REF 123TA8006 – Bulb: H1 24V 70W

REF 151TA3795 - Lens amber

REF 151TA3796 - Lens green

E-approved

TOTAL SOURCE®

REF 151TA3797 - 12V

- Technology: halogen
- Mounting: pole mount
- IP54
- Rotation rate: 160 rotations/minute
- Bulb included


REF 123TA8005 – Bulb: H1 12V 55W

E-approved




ROTATING/FLASHING BEACONS

HALOGEN ROTATING BEACONS




- Technology: halogen
- Mounting: pole mount
- IP55
- Rotation rate: 160 rotations/minute
- 12-24V
- Bulb not included

REF 123TA8006 - Bulb: H1 24V 70W



- Technology: halogen
- Mounting: pole mount
- IP54
- Rotation rate: 160 ± 20 rotations/minute
- Bulb included

REF 150TA4721 - Lens amber


TOTAL SOURCE[®]

- Technology: halogen
- Mounting: pole mount
- IP54
- Rotation rate: 160 ± 20 rotations/minute
- Bulb included

REF 150TA3214 - Lens red

TOTAL SOURCE®


ROTATING/FLASHING BEACONS



- Technology: halogen
- Mounting: pole mount
- Bulb included

TOTAL SOURCE[®]


E-approved



- Technology: halogen
- Mounting: pole mount
- 12–24V
- IP54
- Rotation rate: 160 ± 20 rotations/minute
- Bulb not included

REF 161TA6085 - Bulb: H1 24V 70W

E-approved

TOTAL SOURCE[®]

- Technology: halogen
- Mounting: pole mount
- IP5K4K, IPX9K
- Rotation rate: 160 rotations/minute
- Bulb included



E-approved

ROTATING/FLASHING BEACONS



ROTATING/FLASHING BEACONS


HALOGEN ROTATING BEACONS

REF 151TA3811 – Without bulb

REF 151TA3812 – 12V

REF 151TA3813 – 24V

- Technology: halogen
- Mounting: pole mount
- IP66
- Rotation rate: 160 ± 30 rotations/minute
- Flexible



REF 123TA8005 – Bulb: H1 12V 55W


REF 123TA8006 – Bulb: H1 24V 70W

E-approved

SIRENA s.p.a.

REF 151TA3804 – 12V

- Technology: halogen
- Mounting: pole mount
- IP54
- Rotation rate: 160 rotations/minute
- Bulb included



REF 123TA8005 – Bulb: H1 12V 55W

E-approved

SIRENA s.p.a.


ROTATING/FLASHING BEACONS



XENON FLASHING LIGHT BARS

REF 151TA3821 – 12-24V

- Technology: xenon
- Mounting: magnetic mount
- Wire length: 755 mm
- IP54
- 12V car plug
- Flash rate: 75 ± 10 flashes/minute
- Flash tubes included




REF 151TA3706 – Flash tube

TOTALSOURCE®

REF 151TA3818 – 12-24V

- Technology: xenon
- Mounting: magnetic mount
- Wire length: 755 mm
- IP54
- 12V car plug
- Flash rate: 75 ± 10 flashes/minute
- Flash tubes not replaceable



TOTALSOURCE®

ROTATING/FLASHING BEACONS


ROTATING/FLASHING BEACONS



ROTATING/FLASHING BEACONS

HALOGEN LIGHT BARS

- REF 151TA3816** – 12V
REF 151TA3817 – 24V
- Technology: halogen
 - Mounting: magnetic mount
 - Wire length: 3035 mm
 - IP54
 - 12V car plug
 - Rotation rate: 75 ± 10 rotations/minute
 - Bulbs included




- REF 123TA8005** – Bulb: H1 12V 55W
REF 123TA8006 – Bulb: H1 24V 70W

E-approved

TOTALSOURCE®

- REF 151TA3819** – 12V
REF 151TA3820 – 24V
- Technology: halogen
 - Mounting: central bolt
 - Wire length: 220 mm
 - IP54
 - 12V car plug
 - Rotation rate: 160 rotations/minute
 - Bulbs included



- REF 123TA8005** – Bulb: H1 12V 55W
REF 123TA8006 – Bulb: H1 24V 70W

E-approved

TOTALSOURCE®

ROTATING/FLASHING BEACONS



MAGNETIC LED STROBE LIGHT

1 REF 151TA3829

- Non-rechargeable version
- Powered by battery CR123A (REF 151TA3830)

REF 151TA3832

Rechargeable light without charger

2 REF 151TA3831

Rechargeable version, universal charger included

3 REF 151TA3833

- Case with 6 pieces
- Rechargeable (case recharges all 6 LED lights simultaneously)

Characteristics:

- Height: 34 mm
- Ø 106,50 mm
- 9 different flashing patterns
- Shock-resistant
- Magnetic
- Water-resistant
- With universal charger

These lights can quickly and easily be deployed in case of:


- Works on and along the road
- Vehicle breakdown
- Loading and unloading of a vehicle
- Events

**TOTAL SOURCE®**

XENON EX-PROOF STROBE

REF 151TA3631 - 12-48V

- Technology: xenon
- Mounting: screws
- Length: 80 mm
- With: 75 mm
- Height: 260 mm
- IP66
- Ex-proof
- EX II 2 G, EX II 2 D
- Bulb not replaceable



REF 151TA3632 – Support

REF 151TA3633 – Protection grill

**TOTALSOURCE®**

